



Please forward all material and questions to:

Mark Kislingbury

Production Manager, Journal Division

STA Healthcare Communications Inc.

955 St Jean Boul. Suite 306

Pointe-Claire, Que, H9R 5K3

(514) 695-8393 ext. 204

Technical Specification for High Resolution PDFs

PDF must be level 1.3 or higher

All images must be saved as a single file

-Tiff / EPS Binary encoded only

All images must be in CMYK

Resolution of all images must be at least 225 dpi

Only the use of Postscript fonts is supported

All fonts must be embedded in the PDF file

All colors must be edited accordingly

The trapping must be set to "Default" in Quark Xpress

The offset of crop marks must be set to 12 pts

The bleed must be set to 0.125"

Nothing may be left in the margins of the PFD file

-color bar, test etc...

Imported elements must not be trapped

A Valid color proof is required for press match

- Iris, Rainbow etc...

		Trim	Print area	Bleed
Single page		8"/ 10.875"	7.5"/ 10.375"	0.125"
DPS		16"/ 10.875"	15"/ 10.375"	0.125"
2/3 page	hor.	8"/ 7.5"	7.5"/ 7"	0.125"
	vert.	5.3"/ 10.875"	5"/ 10.375"	0.125"
1/2 page	hor.	8"/ 5.25"	7.5"/ 5"	0.125"
	vert.	4"/ 10.875"	3.75"/ 10.375"	0.125"
1/3 page	hor.	8"/ 3.5"	7.5"/ 3.25"	0.125"
	vert.	2.6"/ 10.875"	2.5"/ 10.375"	0.125"
1/4 page	hor.	8"/ 2.75"	7.5"/ 2.5"	0.125"
	vert.	4"/ 5.25"	3.875"/ 5.125"	0.125"
1/6 page	hor.	8"/ 1.8"	7.5"/ 1.5"	0.125"
	vert.	2.5"/ 5.5"	2.25"/ 5.25"	0.125"

